

**ACCESSORIES FOR SEPARABLE CONNECTORS
FOR SERIE 250 RATING 250 A - INTERFACE A**
formfit®

DEAD-END RECEPTACLE FMR - 250

- EPDM moulding with semi-conducting EPDM jacket. Provides a dead-end facility for insulating bushings.
- Operated when de-energized.
- Watertight, slipped on with silicone grease.
- Supplied with locking brace.
- References : 12 kV - **FMR - 250 - 12**
24 kV - **FMR - 250 - 24**
- Packing : per piece


DEAD-END PLUG FMPD - 250

- EPDM moulding which plugs into the separable connector to provide dead-end facility.
- Operated when de-energized.
- References : 12 kV - **FMPD - 250 - 12**
24 kV - **FMPD - 250 - 24**
- Packing : per piece


STAND-OFF PLUG FMPS - 250

- EPDM moulding designed to support and dead-end the separable connectors when removed from the equipment.
- The stand-off plug is equipped with a metallic bracket. The part in semi-conducting EPDM provides electrical continuity with the outer envelope of the separable connector.
- Operated when de-energized.
- References : 12 kV - **FMPS - 250 - 12**
24 kV - **FMPS - 250 - 12**
- Packing : per piece


EARTHING PLUG FMPE - 250

- EPDM moulding designed to support and earth separable connectors when removed from the equipment.
- The earthing-plug is equipped with a metallic bracket.
- References : **FMPE - 250**
- Packing : per piece

IMPORTANT : before using this product, you must check if it is suitable for your intended application. You assume all risks and liability associated with such use. If any doubt, please consult us.