

Issue date: 29/11/2024

Section 1 Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

G101-123 hot pour bitumen compound.

1.2. Relevant identified uses of the substances or mixture and uses advised against

Encapsulating medium / sealant for power cable joints and terminations.

1.3. Details of the supplier of the safety data sheet**Company information**Prysmian Cables and Systems Ltd
Oak Road, Wrexham Industrial Estate,
Wrexham LL13 9PHPrysmian Cavi e Sistemi Italia S.r.l.
Via Chiese 6
20126 – Milano
Italy**Telephone**

+44 (0) 1978 66 2375

Emailsa.clpsd01gb@prysmiangroup.com**1.4. Emergency telephone number****Emergency telephone number**

+44 (0)1978 66 2216

Poison Centre Information

Country	Organisation	Address	Contact No.
United Kingdom	National Poisons Information Service (Birmingham)	National Poisons Information Service, City Hospital, Dudley Road, B18 7QH, England	0344 892 0111*
Republic of Ireland	Poisons Information Centre of Ireland	National Poisons Information Centre, Beaumont Hospital, Beaumont Road, Dublin 9, Ireland	01 809 2166 01 837 9964*
France	French National Products and Composition Database (B.N.P.C.); French Poison and Toxicovigilance Centre Network	Centre Antipoison de Nancy, CHRU de Nancy, Hôpital Central, 29 av. de Lattre de Tassigny, 54000 NANCY, France	+33 3 83 85 21 92
Germany	BfR Bundesinstitut für Risikobewertung	Max-Dohrn-Str. 8-10, 10589 Berlin	+49 30 18412 0
Italy	Istituto Superiore di Sanità (ISS)	Viale Regina Elena 299, Rome, Italy	
Spain	Instituto Nacional de Toxicología y Ciencias Forenses (INTCF)	Calle José Echegaray 4, 28032 Las Rozas de Madrid, Madrid, Spain	+34 917689800

* For use by healthcare professionals only.

Section 2 Hazards identification

This product is a mixture.

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (EU "CLP" Regulation):
Not classified as hazardous

2.2. Label elements

Labelling according to Regulation (EC) 1272/2008 (EU "CLP" Regulation):
Labelling not required.

2.3. Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB. The mixture does not contain substances identified as having endocrine disrupting properties.

Section 3 Composition / information on ingredients

Hydrogen sulphide may accumulate at hazardous concentrations in confined spaces.

Chemical Name	CAS Number	EC Number	REACH Registration Number	Hazard Class/ Category /Statement	Concentration (w/w%)
Asphalt	8052-42-4	232-490-9	01-2119480172-44-XXXX	-	-

Section 4 First aid measures**4.1. Description of first aid measures***Skin Contact:*

HOT PRODUCT – The affected area should be plunged immediately into cold running water. Do not attempt to remove material adhered to the skin at the worksite. Do not attempt to remove areas of clothing adhered to burnt skin but cut around them. Never use solvent materials for washing of contaminated skin. Seek medical attention in all cases of serious burns.

COLD PRODUCT – Wash contaminated skin with soap and water.

Eye Contact:

HOT PRODUCT – If hot product enters the eye rinse carefully with cold running water to dissipate heat. Obtain medical advice / treatment immediately.

COLD PRODUCT – Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention if irritation, swelling or blurred vision persists.

Inhalation: If there is any suspicion of hydrogen sulphide inhalation remove casualty to fresh air as soon as possible. Begin artificial respiration if breathing has ceased, providing oxygen may help. Obtain medical advice.

Ingestion: Do not induce vomiting. Seek medical attention if symptoms occur. Never give anything by mouth to an unconscious person. Remove victim to fresh air and keep at rest in a position comfortable for breathing.

4.2. Most important symptoms and effects, both acute and delayed.

Skin contact:	Contact with hot / molten product will cause severe burns. Negligible effect at ambient temperature.
Eye contact:	HOT PRODUCT will cause severe burns. COLD PRODUCT will cause minimal redness and irritation.
Inhalation:	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Ingestion:	Few or no symptoms expected. If any, slight nausea may occur.

4.3. Indication of any immediate medical attention and special treatment needed.

Notes to physician: Treatment should in general be symptomatic and directed to relieving any effects. If for any reason the product must be removed, this can be done by using a slightly warmed medicinal liquid paraffin. Bitumen acts as a sterile layer and should only be removed by specialist medical care.

Section 5 Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media: Dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Do not use direct water jet on burning product as this could cause splattering and spread the fire.

5.2. Special hazards arising from the substance or mixture

In the event of a fire or if exposed to excessive heat the resultant pressure build up may result in bursting of the container. Respiratory problems or nausea may be caused by excessive exposure to hot product fumes.

Combustion products comprise solid and liquid particulate matter, hydrogen sulphide, oxides of sulphur and carbon monoxide.

5.3. Advice for firefighters

Remove all persons from the vicinity of the incident. Firefighters should wear appropriate protective equipment and self-contained breathing apparatus incorporating positive pressure face mask conforming to EN469.

Section 6 Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1. For non emergency personnel**

Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. Stop leak if safe to do so. Avoid direct contact with the product. Stay upwind/keep distance from source. In case of large spillages, alert occupants in downwind areas.

Eliminate all ignition sources if safe to do so. Spillages of limited amounts of product, especially in the open air when vapours will be usually quickly dispersed, are dynamic situations, which will presumably limit the exposure to dangerous concentrations.

6.1.2. For emergency responders

SMALL SPILLAGES: normal antistatic working clothes are usually adequate. Wear suitable gloves. Splash goggles.

LARGE SPILLAGES: full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Safety helmet with integrated full face visor and neck protection. antistatic non-skid safety shoes or boots.

Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (and when applicable for H₂S) a Self-Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

6.2. Environmental precautions

Prevent product from entering drains/surface water/ground water. If necessary, dike the product with dry earth, sand or similar non-combustible materials.

6.3. Methods and material for containment and cleaning up

Small spill: Stop leak if without risk. Absorb spilled product with suitable non-combustible materials. Collect solidified product with suitable means (e.g. shovels).

Large spill: When inside buildings or confined spaces, ensure adequate ventilation. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal. Let hot product cool down naturally. If necessary, cautiously use water fog to help the cooling. Do not play direct jets of foam or water on the spilled molten product, as this may cause splattering.

6.4. Reference to other sections

See Section 13 for disposal information.

Section 7 Handling and storage**7.1. Precautions for safe handling**

Do not ingest. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing.

Prevent the risk of slipping. Take precautionary measures against static discharge.

Avoid splash filling of bulk volumes when handling hot liquid product.

7.2. Conditions for safe storage, including any incompatibilities

Store in cool dry location. Keep in original container re-sealed after use. Store separately from oxidising agents.

7.3. Specific end use(s)

See Section 1.2

Section 8 Exposure controls / personal protection

8.1. Control parameters

Bitumen fume:

	8 Hour TWA	15 Min STEL
Bitumen fume:	5 mg/m ³	10 mg/m ³

Hydrogen Sulphide:

	8 Hour TWA	15 Min STEL
Hydrogen Sulphide	7 mg/m ³ 5 ppm	14 mg/m ³ 10 ppm

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Do not ingest. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing.

Prevent the risk of slipping. Take precautionary measures against static discharge.

Avoid splash filling of bulk volumes when handling hot liquid product.

8.2.2. Individual protection measures

Hand protection: Heat resistant gloves with long cuffs, or gauntlets (EN 374 - 407). Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

Body protection: Wear protective clothing for operations with hot material: heat resistant coveralls (with trousers legs over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid boots (e. g. leather). Coveralls should be changed at the end of the work shift and cleaned as necessary to avoid transfer of product to clothes or underwear.

Skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection: Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H₂S) or self-contained breathing apparatus (SCBA).

8.2.3. Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 9 Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Solid at 20 °C
Colour:	Dark brown/black
Odour:	Bitumen
Odour threshold:	No data available
Melting point:	No data available
Freezing point:	No data available
Boiling point:	> 320 °C
Flammability:	No data available
Lower explosion limit:	No data available
Upper explosion limit:	No data available
Flash point:	> 240 °C (Closed cup) > 220 °C (Open cup)
Auto-ignition temperature	> 300 °C
Decomposition temperature	> 350 °C
pH:	Not applicable
Viscosity, kinematic:	Not applicable
Solubility:	Insoluble in water
Partition coefficient n-octanol/water: (Log K _{ow}):	Not applicable
Vapour pressure:	100 Pa at 20 °C
Vapour pressure at 50°C	No data available
Density:	0.99 to 1.10 g/cm ³ at 25 °C
Relative density:	Not applicable
Relative vapour density at 20°C	Not applicable
Particle characteristics	Does not contain nanomaterials

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

No additional information available.

9.2.2. Other safety characteristics

No additional information available.

Section 10 Stability and reactivity**10.1. Reactivity**

Not reactive to materials commonly used in the transportation, handling and storage of industrial materials.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions unknown.

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Store away from oxidising agents.

10.6. Hazardous decomposition products

Incomplete combustion will generate oxides of in evolution of carbon, sulphur and nitrogen.

Section 11 Toxicological information

11.1. Information on toxicological effects

Component	Test	Route	Species	Duration	Result
Bitumen	LC50	Inhalation, vapour	Rat	4hrs	> 94.4 mg/m ³
	LC50	Dermal	Rabbit	4hrs	> 5000 mg/kg
	LC50	Oral	Rat	4hrs	> 5000 mg/kg

No other known significant effects or critical hazards.

11.2. Information on other hazards

The mixture does not contain substances identified as having endocrine disrupting properties.

Section 12 Ecological information

12.1. Toxicity

No significant effects or critical hazards.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely.

12.4. Mobility in soil

Not mobile when cooled to a solid.

12.5. Results of PBT and vPvB assessment

This mixture does not contain any REACH registered substances assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

The mixture does not contain substances identified as having endocrine disrupting properties.

12.7. Other adverse effects

No data available.

Section 13 Disposal considerations**13.1. Waste treatment methods**

Product:	Not hazardous waste. Waste product should be sent for disposal in accordance with local authority regulations by licensed operators, controlled incineration or controlled landfill.
Packaging:	Not hazardous waste. Used containers should be sent for disposal in accordance with local authority regulations by licensed operators, controlled incineration or controlled landfill.
Local legislation	
Waste catalogue:	EU Waste Disposal Code (EWC)
Waste code:	01 01 17 BITUMEN

Section 14 Transport information**14.1. UN number or ID number**

The cold (solid) product is not classified as hazardous for transport.

14.2. UN proper shipping name

The cold (solid) product is not classified as hazardous for transport.

14.3. Transport hazard class

The cold (solid) product is not classified as hazardous for transport.

14.4. Packing group

The cold (solid) product is not classified as hazardous for transport.

14.5. Environmental hazards

Not regulated under transport regulation.

14.6. Special precautions for user

For transport within user's premises: Always transport in upright sealed container.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable to the cold (solid) material.

Section 15 Regulatory information

This Safety Data Sheet has been prepared in accordance with the requirements of regulation (EC) No 1907/2006 as amended.

Labelling elements as classified under Regulation (EC) 1272/2008.

The Workplace exposure Limit given in Section 8 has been taken from the UK HSE document: EH40/2005 Workplace Exposure Limits as amended.

Additional relevant regulations:

Regulation (EC) 790/2009 First Adaptation to Technical Progress (ATP) for CLP regulation

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

None applicable.

15.2. Chemical safety assessment

A chemical safety assessment has not been undertaken for this mixture.

Section 16 Other information

This SDS (version 4.0) is the 4th version of this SDS for this product.

This information is believed to be accurate and represents the best information available to the company at this time. This information is provided as a guide to the hazards and respective safety precautions relevant to this product. This SDS does not represent any guarantee of performance or specification. The information relates only to the product specified and may not be suitable for combinations with other materials or in processes other than those specifically described herein.